


VALKYRIE C


Conventional Wall Sounder



Available in 2 colours  

The Valkyrie C is a low consumption sounder/ beacon designed to be used as an unobtrusive low profile wall sounder. This improves the aesthetics of the fire alarm system. Four different tones are available and selected using DIL switches 1 and 2. The Sound level can be lowered if required by setting DIL switch no. 4 to ON.

Valkyrie - Dimensions




TONE CONFIGURATIONS

Switch 1 and 2
Tone Selection

Switch 3
Spare

Switch 4
High-Low Volume Selector



Technical Specifications

Supply Voltage	17V to 30 V DC
Current - Quiescent	0.5 mA
Current -Alarm Low. Freq.	4.1 mA (Max.) - 2.6 mA (Min.)
Current -Alarm High. Freq.	7.5 mA (Max.) - 3 mA (Min.)
Current -Alarm Beacon	1.4 mA
Sounder Output - Continuous	102 dB @ 1 m (Max.) - 97 dB @ 1 m (Min.)
Sounder Output - Low Freq.	103 dB @ 1 m (Max.) - 98 dB @ 1 m (Min.)
Sounder Output - High Freq.	110 dB @ 1 m (Max.) - 100 dB @ 1 m (Min.)
Max. Cable Size	2.5 mm ²
Max. Humidity	85% RH Non-Condensing
Operating Temperature	0 °C to 40 °C
Enclosure - Material	Red/ White ABS - FR rating 94V0
Protection Category	IP44
Dimensions	109.5 mm (Dia) x 83.6 mm (H)
Weight	125 g
Order Code	
VALKYRIE CS	Valkyrie Conventional Wall Sounder
VALKYRIE CSB	Valkyrie Conventional Wall Sounder/ Beacon

Global Fire Equipment S.A.

MARF - Armazens F3 e F4, Sítio do Guelhim, Estoi, 8009-021 FARO, PORTUGAL

Tel: + 351 289 896 560 Fax: + 351 289 865 587



Sales sales@globalfire.pt **Technical Support** techs@globalfire.pt